

WHEN COMPLETE, RETURN TO: City of Sedona Engineering Services 102 Roadrunner Drive Sedona, AZ 86336

> Phone: (928) 204-7111 Fax: (928) 282-4358 TDD: (928) 204-7102

## Sidewalk/Curb Cut Complaint Or Assistance Request Form

Please be advised that this form is a matter of public record and will be disclosed upon request.

1.	List the name of street/intersection believed to be in violation of the Americans with Disabilities Rules and Regulations. Please give exact street locations. For example, the street address or intersection with cross street. (Use a separate form for each street/intersection.)				
	Address:				
2.	Is the sidewalk(s) or curb(s) currently under construction, repair or reconstruction? YESNO				
	Have the sidewalk(s) or curb(s) been repaired, reconstructed or constructed? YESNO WHEN:				
3.	Please check the following items which you believe are in violation:				
	Curb Cuts and Ramps				
Curb cuts are not provided where an accessible route crosses a curb.					
	Curb cut is not provided at each corner of intersection, located within the crosswalk and/or the pedestrian path of travel.				
	Curb cut is not perpendicular to the curb at street crossings and/or does not have a level landing at the top.				
	At marked crossings, the bottom of the ramp run, exclusive of flared sides, is not contained within the marked crossing.				
	Curb cuts or sidewalks are being constructed or reconstructed on one side of the street, and curb cuts are not provided on the opposite side of the street.				
	Curb cuts are not provided at driveways intersecting sidewalks when the driveway has side curbs.				

Raised island in crossing is not cut through level with the street and/or does not have curb cuts at both sides and a level area at least 48 inches long between the curb cuts in the part of the island intersected by the crossings.			
Curb cuts are obstructed by parked vehicles.			
Maximum slope exceeds 1:12 (8.3%).			
Transition from curb cut to walk, gutter or street is greater than ½ inch high.			
Grading and drainage are not designed to minimize water pooling, ice accumulation or water flowing at the bottom of the curb cut.			
Minimum width of a curb cut is less than 36 inches, exclusive of flared sides.			
A landing at the top of the curb cut is not 48 inches in length. The slope of said landing exceeds 1:50 (2%) in any direction.			
Sides of curb cuts are less than 24 inches at the curb. Maximum flare slope exceeds 1:10 (10%).			
Curb cuts with returned sides are provided and are not protected by handrails, street furniture or landscaping.			
Cross-slope of sidewalk exceeds 1:50 (2%).			
Built-up curb cut is provided which projects into vehicular traffic lanes.			
<u>Crosswalks</u>			
Cross-slope exceeds 1:50 (2%).			
Maximum longitudinal slope exceeds 1:12 (8.33%).			
Pedestrian Street Crossing Controls (if provided)			
Controls are not raised from or flush with their housings and/or are not a minimum of two inches in the smallest dimension.			
Force required to activate controls exceeds 5 ft-lb.			
Controls are not located as close as practicable to the curb cut serving the controlled crossing and/or do not permit operation from a clear ground space.			
Pedestrian-actuated controls are not at maximum of 42 inches above sidewalk.			

	A stable and firm area, complying with Forward Reach or Side Reach, is not at the controls.	t provided
	Where a parallel approach is provided, controls are not within ten inches he of and/or are not centered on the clear ground space. Where a forward approvided, controls do not abut and/or are not centered on the clear ground space.	proach is
1.	What was the most recent date you observed the violation?	
5.	Name and address of person/organization filing this complaint:	
	Telephone:	
	If organization is filing, please provide name of contact person.	
5.	SIGNATURE: (Form must be signed by an individual.)	
	DATE	
7.	RECEIVED BY:	
	DATE	
	TIME:	