

PRELIMINARY WASTEWATER REPORT

Prepared for:
RD Olson Development
150 Schnebly Hill Road
Sedona, Arizona 86336



July 17, 2023

Prepared by:





Luke Sefton PE, CFM
Timothy Huskett, P.E., CFM
Dugan McDonald, R.L.S.
Clint Gillespie, R.L.S.
Sam Musser, Planner

TABLE OF CONTENTS

General Location and Description..... 1
 Project Overview 1
 Project Location..... 1
 Property Owner/Developer..... 1
Design of Wastewater Collection System 1
 Design Flow..... 1
 Design Criteria 1
 Design Specification 3
Conclusion..... 3

APPENDICES

Appendix A – Preliminary Utility Plan





Luke Sefton PE, CFM
Timothy Huskett, P.E., CFM
Dugan McDonald, R.L.S.
Clint Gillespie, R.L.S.
Sam Musser, Planner

Utilizing the ADEQ sewerage flows, the total average daily flow of **8,810** gallons will be routed through the proposed on-site gravity sewer system. The total peak flow is **31,716** gallons per day.

Design Criteria

1. The proposed gravity wastewater collection system was designed in accordance with Arizona Administrative Code Title 18, Chapter 9, Article 3 Aquifer Protection Permit: Part E Type 4 General Permits, Uniform Plumbing Code 2015 edition, and standard engineering practices.
2. Separation of wastewater collection system components from drinking water distribution system shall be in accordance with A.A.C. R18-5-502. According to the aforementioned section, a water main shall not be placed within 6 feet, horizontal distance, and below 2 feet, vertical distance, above the top of a sewer main unless extra protection is provided. Extra protection shall consist of construction of the sewer main with mechanical joint ductile iron pipe or with slip-joint ductile iron pipe if joint restraint is provided. Alternative extra protection shall consist of encasing both the water and sewer in at least 6 inches of concrete for at least 10 feet beyond the area covered by this subsection C.1.a. A watermain shall not be placed within 2 feet horizontal and 2 feet below the sewer main. No water pipe shall pass through or come into contact with any part of a sewer manhole. The minimum horizontal separation between water mains and manholes shall be 6 feet, measured from the center of manhole.
3. A minimum 3-foot ground cover is required over sanitary sewer main lines according to A.A.C. R18-9-E301 subsection D.2.b while meeting the requirements of subsection D.2.h. for sewer bedding and trenching.
4. A minimum 1-foot cover is required over sewer service lines in accordance with Section 718.3 of the Uniform Plumbing Code.
5. Public Sewer main lines shall be a minimum of 8 inches in diameter according to A.A.C. R18-9-E301 subsection D.2.d. except for the first 400 feet of a dead-end sewer line with no potential for extension.
6. Sewer service lateral and water service line separation shall be in accordance with Section 720.1 of the Uniform Plumbing Code which states the bottom of the water pipe, at all points, shall be at least 12-inches above the top of the sewer line.
7. The sewer system in excessive slopes is designed according to A.A.C. R-18-9-E301 subsection D.2.f. According to the aforementioned section, any sewer line carrying a flow with a normal velocity of greater than 10 feet per second shall be constructed with ductile iron pipe or pipe with equivalent erosion resistance and structurally reinforces the receiving manhole or sewer main.
8. Each sewer line shall be tested per A.A.C. R-18-9-E301 subsection D.2.j.i. which states that each segment of sewer line shall be tested for leakage in accordance with ASTM F1417-92.
9. Each sewer line shall be tested according to A.A.C. R18-9-E301 subsection D.2.i. which states that a deflection test shall be performed for the total length of all sewer lines made of flexible



Luke Sefton PE, CFM
Timothy Huskett, P.E., CFM
Dugan McDonald, R.L.S.
Clint Gillespie, R.L.S.
Sam Musser, Planner

material to ensure that the installation meets or exceeds the manufacturer's recommendations and results be recorded.

10. Each sewer line shall be tested according to A.A.C. R18-9-E301 subsection D.2.k. which states that the sewer line shall be tested for uniform slope by lamp lighting, remote camera or similar method and results be recorded.
11. Each manhole shall be tested according to A.A.C. R18-9-E301 subsection D.3.e. which states that each manhole be tested using one of the following test protocols: Watertight Testing, Negative Air Pressure Testing, or Holiday Testing.

Design Specifications

1. The proposed wastewater collection system will be constructed using SDR 26 pipe for the 8-inch on-site collection main lines and 4-inch lateral service lines.
2. Proposed pre-cast sewer manholes will be installed in accordance with MAG Standard Detail 420-1 & 420-2.
3. A typical 8-inch SDR 26 sewer pipe at a minimum slope of 1.0 percent has a capacity of 0.85 MGD. The proposed 8-inch sewer collection system serving the development has a calculated design flow of 8,810 gallon per day, which is significantly lower than the maximum flow capacity of a typical 8-inch sewer pipe. With a Manning's Roughness Coefficient of 0.013 the proposed 8-inch pipe flowing full will have a velocity of 3.8 feet per second.
4. All sewer service connections will be a 4-inch PVC SDR 26 pipe with a double cleanout and a 45-degree wye at the sewer main connection. The separation requirements do not apply to building plumbing, or individual house service connections per A.A.C. R18-5-502 subsection C.4.
5. Manholes will be spaced at no greater than 500 feet intervals for all sewer main lines. All sewer service laterals will have 4-inch cleanouts spaced no greater than 100 feet along their length and end with a 4-inch cleanout.
6. Units with finished floor elevations below the next downhill manhole rim elevation will be equipped with an approved backflow preventer valve.

CONCLUSION

It is the engineer's opinion that the property be developed as shown on the approved construction plans. The wastewater system shown on the plans will satisfy the conditions for a cost-effective, low maintenance wastewater facility. The project complies with the City of Sedona and the Arizona Department of Environmental Quality wastewater regulations and standards.

Appendix A

Preliminary Utility Plan


40 Stutz Bearcat Dr., Sedona, Arizona 86336 ~Phone: (928) 202-3999
Email: info@sefengco.com ~ www.SeftonEngineeringCompany.com

In affiliation with:

Heritage Land Surveying & Mapping, Inc. with office in Sedona, Camp Verde & Colorado

KEY NOTES:

- ① 4" SEWER SERVICE LINE WITH DUAL DIRECTION CLEANOUT AT BUILDING AND UNI DIRECTIONAL CLEANOUT AT BEND. (SEE DETAILS).
- ② 1" WATER SERVICE.
- ③ 200A UNDERGROUND ELECTRIC SERVICE
- ④ GAS SERVICE LINE AND METER
- ⑤ LOCATION OF TEMPORARY CONSTRUCTION DUMPSTER
- ⑥ LOCATION OF TEMPORARY PORT-A-JOHN
- ⑦ PAVER DRIVEWAY AND WALKWAY WITH EDGING.
- ⑧ CRUSHED GRANITE WALKWAY
- ⑨ STEM WALL
- ⑩ CONSTRUCTION ENVELOPE FENCE TO BE LIMIT OF DISTURBANCE AND SHALL PROTECT TREES TO REMAIN.
- ⑪ NATURAL ROCK LANDSCAPE WALL. (SEE DETAIL).
- ⑫ DOWNSPOUT CONNECTED TO UNDERGROUND DRAIN PIPE.
- ⑬ 36" x 24" x 3" DEEP LANDSCAPE ROCK PADS UNDERNEATH ALL DOWNSPOUTS NOT CONNECTED TO DRAIN PIPE AND AT DRAIN PIPE OUT FLOW LOCATIONS.
- ⑭ YARD DRAIN. (SEE GRADING & DRAINAGE PLAN).
- ⑮ UNDERGROUND DRAIN PIPE. (SEE GRADING & DRAINAGE PLAN).
- ⑯ DETENTION POND. (SEE GRADING & DRAINAGE PLAN).



PRELIMINARY

40 STUTZ BEARCAT DR. #8
 SCOTSDALE, ARIZONA 86336
 PH: (928) 202-3995 LS@SEFTONCO.COM

<p>SANITARY SEWER PLAN</p> <h1 style="margin: 0;">OAK CREEK HERITAGE HOTEL</h1> <p style="margin: 0;">R.D. OLSON DEVELOPMENT</p>	
SHEET TITLE: PROJECT TITLE: DRAWN BY: SCALE: DATE: PROJECT NO: SHEET NO.	<p>TCH</p> <p>1" = 40'</p> <p>DATE</p> <p>201106</p> <p style="font-size: 2em; font-weight: bold; text-align: center;">C-1</p>

© 2022, Sefton Engineering Consultants LLC, All Rights Reserved. This document is protected under the United States Copyright Act. No part may be reproduced in any form or by any means or stored in a database or retrieval system, without the prior written permission of Sefton Engineering Consultants, LLC. These plans/documents have been prepared using technical knowledge that would be applied by other qualified registrants who practice the same profession in the same area and at the same time. Efforts have been made to be as accurate as possible. However, plans/documents could contain unintentional technical inaccuracies, typographical errors or omissions. Users of these plans/documents should understand that it is highly probable that errors and omissions will occur in any plan/document preparation process, the user shall notify and registerate for substitution.